



- NOTES/SPECIFICATIONS:
  1. DESIGN WAVELENGTH: 587.6nm
- FOCAL LENGTH: f=19.9mm ± 1%
- 2. BACK FOCAL LENGTH(REF): bf=18.3mm CLEAR APERTURE: >90%
- SURFACE QUALITY: 40-20 SCRATCH-DIG 5.
- 6. CENTRATION: <3arcmin
- 7. DIAMETER TOLERANCE: +0.0/-0.1mm
- 8. THICKNESS TOLERANCE: ±0.1mm
- COATING: BBAR Ravg<0.5% FROM 350nm-700nm, 0° AOI, ON OUTER OPTICAL SURFACES

ALL DIMENSIONS ARE IN THE FORM  $\frac{[in]}{mm}$ 

THIS DRAWING IS FOR INFORMATION ONLY NOT INTENDED FOR MANUFACTURING

			THORLA	BS II	NC. PO NEW	BOX VTON	366 I NJ
	NAME	DATE	TITLE: D=9.0 F=20.0 N-BK7 A COAT PLANO CONVEX LENS				
DRAWN	WD	11/19/2009					
ENG APPR.	BW	11/24/2009					
MFG APPR.	DD	12/09/2009					DE) /
PROPRIETARY AND CONFIDENTIAL			N-BK7			SIZE	REV.
THE INFORMATION CONTAINED IN THIS			SCALE: 6:1				
DRAWING IS THE SOLE PROPERTY OF THORLABS, INC. ANY REPRODUCTION			3CALE. 6.1		SHEET 1 OF 1		
IN PART OR AS A WHOLE WITHOUT			DWG. NO.	PART N	NO.		

4416-E01

LA1472-A

3 2

THE WRITTEN PERMISSION OF

THORLABS, INC. IS PROHIBITED.