



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 4 μ m
2. FOCAL LENGTH: f= -20.0mm \pm 2%
3. BACK FOCAL LENGTH(REF): bf= -19.9mm
4. CLEAR APERTURE: > ϕ 11.43mm
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION: <3arcmin
7. DIAMETER TOLERANCE: +0.0/-0.1mm
8. THICKNESS TOLERANCE: \pm 0.1mm
9. COATING: BBAR Ravg<1.25% FROM 2.0-5.0 μ m, 0 $^\circ$ AOI ON BOTH OPTICAL SURFACES

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THORLABS www.thorlabs.com CaF ₂ - MENISCUS LENS, ϕ 12.7mm, f= -20mm, BBAR: 2.0-5.0 μ m	
NAME	DATE			
DRAWN	KMR	21/MAY/18	MATERIAL VACUUM UV GRADE CALCIUM FLUORIDE	
APPROVAL	BW	21/MAY/18		
COPYRIGHT © 2018 BY THORLABS VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			ITEM #	APPROX WEIGHT
			LF5067-E	1.4g