

## NOTES/SPECIFICATIONS:

- CLEAR APERTURE: >90% DIAMETER
  SURFACE ACCURACY: \(\lambda/4\) AT 632.8nm OVER CLEAR APERTURE
  SURFACE QUALITY: 40-20 SCRATCH-DIG
  BACK SURFACE: FINE GROUND
  THICKNESS TOLERANCE: \(\pma\).2 mm
  DIAMETER TOLERANCE: \(\pma\).0/-0.2 mm
  COATING: PROTECTED GOLD
  Ravg: \(\pma\)96% FROM 800nm 20\(\pm\)
  AOI: 0° TO 45°
  DAMAGE THRESHOLD: 2J/cm² 10ns PULSE, 10Hz AT 1064nm

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THORLABS.com		
	NAME	DATE	Ø 25.4mm, f= 100.0mm CONCAVE		
DRAWN	BAG	28/OCT/10	PROTECTED GOLD MIRROR		
APPROVAL	WD	08/NOV/12	MATERIAL		REV
COPYRIGHT © 2010 BY THORLABS			N-BK7		С
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS			CM254-100-M01	APPROX WE 0.007	ight kg