



NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: $> \varnothing 22.86\text{mm}$
2. SURFACE IRREGULARITY (S1): $\leq \lambda/4$ AT 633nm OVER CLEAR APERTURE
3. BACK SURFACE (S2): UNIFORM FINE GRIND #12-#20 GRIT
4. SURFACE QUALITY(S1): 40-20 SCRATCH-DIG
5. THICKNESS TOLERANCE: $\pm 0.1\text{ mm}$
6. DIAMETER TOLERANCE: $+0.0/-0.2\text{ mm}$
7. COATING(S1): PROTECTED GOLD
 $R_{\text{avg}}: >96\%$ FROM 800nm-20 μm
 AOI: 0° TO 45°

FOR INFORMATION ONLY
 NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			 www.thorlabs.com $\varnothing 25.4\text{mm}$, f=500mm CONCAVE PROTECTED GOLD MIRROR	
DRAWN	NAME	DATE		
APPROVAL	YB	DD	16/APR/18	MATERIAL
COPYRIGHT © 2018 BY THORLABS VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			16/APR/18	N-BK7
ITEM #		APPROX WEIGHT		REV
CM254-500-M01		7.68 g		A