

## NOTES/SPECIFICATIONS:

- CLEAR APERTURE: >90% DIAMETER
  SURFACE ACCURACY: \(\lambda/4\) AT 632.8nm OVER CLEAR APERTURE
  SURFACE QUALITY: 20-10 SCRATCH-DIG
  BACK SURFACE: FINE GROUND
  THICKNESS TOLERANCE: \(\pma\).2 mm
  DIAMETER TOLERANCE: \(\pma\).0/-0.2 mm
  COATING: BROADBAND HR, DIELECTRIC
  RS and Rp >99% OVER WAVELENGTH RANGE
  AOI: 0° TO 45°

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

	DRAWING PROJECTION			THORLASS www.thorlabs.com			
		NAME	DATE	$\emptyset$ 25.4mm, f= 50.0mm BROADB		AND	
	DRAWN	MG	15/JUN/11	MIRROR 350-400nm		,_	
	APPROVAL	PM	13/JUL/11	MATERIAL		REV	
	COPYRIGHT © 2010 BY THORLABS			N-BK7		Α	
	VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS			CM254-050-E01	0.007 kg		