





NOTES/SPECIFICATIONS:

- 1. 2. 3. 4. 5. 6. 7. 8. 9.

- DESIGN WAVELENGTH: 10.6 µm
 FOCAL LENGTH: f=15.0 mm±1%
 BACK FOCAL LENGTH(REF): bf=13.8 mm
 CLEAR APERTURE: > Ø 10.2 mm
 SURFACE QUALITY (\$1, \$2): 60-40 SCRATCH-DIG
 CENTRATION: <3 arcmin
 DIAMETER TOLERANCE: +0.0/-0.1 mm
 THICKNESS TOLERANCE: ±0.1 mm
 COATING (\$1, \$2): BBAR 4.5-7.5 µm, Ravg: <1.0%, Rabs: <2.0%, Tavg: >97%, Tabs: >94%, 0° AOI

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION THORLABS WWW.thorlabs.com					
	NAME	DATE	ZnSe PLANO-CONVEX LENS.		
DRAWN	GG	30/MAY/19	Ø 12.7 mm, f=15 mm, BBAR: 4.5-7.5 μm		μm
APPROVAL	DD	30/MAY/19	MATERIAL REV		REV
COPYRIGHT © 2019 BY THORLABS			ZINC SELENIDE		Α
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS			ITEM # LA7477-E2	APPROX WE	IGHT