





NOTES/SPECIFICATIONS:

- CLEAR APERTURE: >90% DIAMETER
 SURFACE ACCURACY: \(\lambda/4\) AT 632.8nm OVER CLEAR APERTURE
 SURFACE QUALITY: 40-20 SCRATCH-DIG
 BACK SURFACE: FINE GROUND
 THICKNESS TOLERANCE: \(\pma\).2 mm
 DIAMETER TOLERANCE: \(\pma\).0/-0.2 mm
 COATING: PROTECTED GOLD
 Ravg: \(\pma\)96% FROM 800nm 20\(\pm\)
 AOI: 0° TO 45°
 DAMAGE THRESHOLD: 2J/cm² 10ns PULSE, 10Hz AT 1064nm

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THORLASS www.thorlabs.com		
	NAME	DATE	Ø25.4mm, f= 75.0mm CONCAV		VF
DRAWN	BAG	28/OCT/10	PROTECTED GOLD MIRROR		
APPROVAL	WD	08/NOV/12	MATERIAL		REV
COPYRIGHT © 2010 BY THORLABS			N-BK7		С
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS			ITEM # CM254-075-M01	APPROX WE	iGHT ka