



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 588nm
2. FOCAL LENGTH: $f = -30.0\text{mm} \pm 1\%$
3. BACK FOCAL LENGTH(REF): $bf = -32.1\text{mm}$
4. CLEAR APERTURE: >90% OF DIAMETER
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION: $\leq 3\text{arcmin}$
7. DIAMETER TOLERANCE: $+0.0/-0.1\text{mm}$
8. THICKNESS TOLERANCE: $\pm 0.1\text{mm}$
9. COATING: BBAR $R_{\text{avg}} < 0.5\%$ FROM 1050nm-1700nm, 0° AOI, ON OUTER OPTICAL SURFACES

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THORLABS www.thorlabs.com D=25.4mm F=-30.0mm UVFS PLANO CONCAVE LENS, -C COAT	
	NAME	DATE		
DRAWN	GG	28/SEP/12	MATERIAL UV GRADE FUSED SILICA	
APPROVAL	DD	12/MAR/15		
COPYRIGHT © 2015 BY THORLABS			ITEM #	APPROX WEIGHT
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			LC4252-C	0.03 kg
			REV	B