



NOTES/SPECIFICATIONS:

- 1. 2. 3. 4. 5. 6. 7. 8. 9.

- DESIGN WAVELENGTH: 588nm FOCAL IENGTH: 500.0mm ± 1% BACK FOCAL LENGTH (REF): 498.4mm CLEAR APERTURE: >22.86mm SURFACE QUALTIY: 40-20 SCRATCH-DIG CENTRATION: <3 arcmin DIAMETER TOLERANCE: +0.0/-0.1mm THICKNESS TOLERANCE: ±0.1mm COATING: BBAR Ravg <1.25% FROM 2µm-5µm, 0° AOI ON BOTH OPTICAL SURFACES

FOR INFORMATION ONLY	
NOT FOR MANUFACTURING PURPOSES	

DRAWIN PROJECT	G		www.thorlabs.com CaF2 PLANO-CONVEX LENS, Ø 25.4mm, f=500.0mm, BBAR: 2µm-5µm		
	NAME	DATE			
DRAWN	EMT	20/JAN/14			
APPROVAL	MI	08/APR/14	VACUUMUVGRADE		REV
COPYRIGHT © 2014 BY THORLABS		Y THORLABS	CALCIUM FLUORIDE B		В
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS			ITEM # LA5464-E	APPROX WE 3.50	IGHT