



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 10.6 μm
2. FOCAL LENGTH: $f=1,000.0\text{ mm} \pm 1\%$
3. BACK FOCAL LENGTH(REF): $bf=999.1\text{ mm}$
4. CLEAR APERTURE: $> \varnothing 20.3\text{ mm}$
5. SURFACE QUALITY: 60-40 SCRATCH-DIG
6. CENTRATION: $< 3\text{ arcmin}$
7. DIAMETER TOLERANCE: $+0.0/-0.1\text{ mm}$
8. THICKNESS TOLERANCE: $\pm 0.1\text{ mm}$
9. COATING: BBAR $R_{avg} < 3.5\%$, $R_{abs} < 6\%$, $T_{avg} > 92\%$, $T_{abs} > 85\%$, 2.0-13.0 μm , AOI: 0° ON BOTH OPTICAL SURFACES

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THORLABS www.thorlabs.com ZnSe PLANO-CONVEX LENS, $\varnothing 25.4\text{ mm}$, $f=1,000\text{ mm}$, BBAR: 2.0-13.0 μm	
	NAME	DATE		
DRAWN	GG	05/OCT/17	MATERIAL ZINC SELENIDE	
APPROVAL	DD	05/OCT/17		
COPYRIGHT © 2020 BY THORLABS			ITEM #	APPROX WEIGHT
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			LA7753-E4	5 g
			REV	A