



CONNECTOR: HIROSE HR25-7TP-8S(72)

PIN	DESCRIPTION	CABLE COLOR
1	GROUND	GRAY
2	FLASH OUTPUT, OPTO-DECOUPLED (-)	GREEN
3	GPIO 1, 3.3V LVCMOS	BLUE
4	TRIGGER INPUT, OPTO-DECOUPLED (-)	BROWN
5	FLASH OUTPUT, OPTO-DECOUPLED (+)	YELLOW
6	GPIO 2, 3.3V LVCMOS	RED
7	TRIGGER INPUT, OPTO-DECOUPLED (+)	WHITE
8	OUTPUT SUPPLY VOLTAGE, 5V (100mA)	PINK

FOR INFORMATION ONLY  
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			<b>THORLABS</b> www.thorlabs.com	
	NAME	DATE	I/O CABLE FOR DCC3240	
DRAWN	Hit.	21/MAR/13	MATERIAL	
APPROVAL	Ge	21/MAR/13	N.A.	REV A
COPYRIGHT © 2013 BY THORLABS			ITEM #	APPROX WEIGHT
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			CAB-DCU-T3	0.08kg