COPYRIGHT © 2006 by THORLABS INC. **ROTARY GAIN SWITCH** [3.1] 0.12 POWER SWITCH: 8 POSITION DETECTOR SURFACE 0.80 [27.4] 1.08 DETAIL A [70.1] SCALE 2:1 2.76 [53.3] 2.10 [22.4] [20.1] 0.88 0.79 0.535-40 INTERNAL THREAD MATES WITH SM05 LINE POWER SUPPLY-POWER IN CONNECTOR [43.2] [52.3] LED POWER. [48] 1.70 2.06 **INDICATOR** 1.89 (0) 0 **OUTPUT BNC WITH** OUTPUT 0 TO 10v RANGE 0-10V 1.035-40 EXTERNAL THREAD #8-32 X 0.25" THREAD MATES WITH SM1 LINE 0.50 THORLABS INC. PO BOX 366 NEWTON NJ NAME DATE TITLE: EC 3/28/2006 DRAWN EC GaP Amplified Detector ENG APPR. 3/28/2006 EC MFG APPR. 3/28/2006 MATERIAL: SIZE REV. PROPRIETARY AND CONFIDENTIAL PDA25K Α С THE INFORMATION CONTAINED IN THIS SCALE: 1:1 SHEET 1 OF 1 DRAWING IS THE SOLE PROPERTY OF THORLABS, INC. ANY REPRODUCTION DWG. NO. PART NO. IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF 13050-E0W PDA25K THORLABS, INC. IS PROHIBITED.

5 3 2