



NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: >90% DIAMETER
2. SURFACE ACCURACY: $\lambda/4$ AT 632.8nm OVER CLEAR APERTURE
3. SURFACE QUALITY: 40-20 SCRATCH-DIG
4. BACK SURFACE: FINE GROUND
5. THICKNESS TOLERANCE: ± 0.2 mm
6. DIAMETER TOLERANCE: + 0.0/-0.2 mm
7. COATING: PROTECTED GOLD
 R_{avg} : >96% FROM 800nm - 20 μ m
 AOI: 0° TO 45°
8. DAMAGE THRESHOLD: 2J/cm² 10ns PULSE, 10Hz AT 1064nm

FOR INFORMATION ONLY
 NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THORLABS www.thorlabs.com	
NAME	DATE			
DRAWN	BAG	28/OCT/10	ϕ 12.7mm, f= 25.0mm CONCAVE PROTECTED GOLD MIRROR	
APPROVAL	WD	08/NOV/12	MATERIAL	REV
COPYRIGHT © 2010 BY THORLABS			N-BK7	C
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS		ITEM #	APPROX WEIGHT	
		CM127-025-M01	0.002 kg	