



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 587.6nm
2. FOCAL LENGTH:  $f=175.6\text{mm} \pm 1\%$
3. BACK FOCAL LENGTH(REF):  $bf=173.6\text{mm}$
4. CLEAR APERTURE: >90% OF DIAMETER
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION: <3arcmin
7. DIAMETER TOLERANCE:  $+0.0/-0.1\text{mm}$
8. THICKNESS TOLERANCE:  $\pm 0.1\text{mm}$
9. COATING: BBAR  $R_{avg} < 0.5\%$  FROM 1050nm-1700nm,  $0^\circ$  AOI, ON OUTER OPTICAL SURFACES

FOR INFORMATION ONLY  
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			<b>THORLABS</b> <a href="http://www.thorlabs.com">www.thorlabs.com</a>	
NAME	DATE			
DRAWN	GG	28/SEP/12	D=25.40 F=175.6 UV FUSED SILICA PLANO CONVEX LENS, -C COAT	
APPROVAL	DD	28/APR/15	MATERIAL	REV
COPYRIGHT © 2015 BY THORLABS			UV FUSED SILICA	B
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			ITEM #	APPROX WEIGHT
			LA4924-C	0.03 kg