







NOTES/SPECIFICATIONS:

- 1. 2. 3. 4. 5. 6. 7.

- CLEAR APERTURE: >90% DIAMETER SURFACE ACCURACY: \/4 AT 632.8nm OVER CLEAR APERTURE SURFACE QUALITY: 40-20 SCRATCH-DIG BACK SURFACE: FINE GROUND THICKNESS TOLERANCE: ±0.2 mm DIAMETER TOLERANCE: ±0.2 mm COATING: PROTECTED GOLD Ravg: >96% FROM 800nm 20µm AOI: 0° TO 45° DAMAGE THRESHOLD: 2J/cm² 10ns PULSE, 10Hz AT 1064nm
- 8.

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION					
	NAME DATE \emptyset 12.7mm, f= 50.0mm CONC/		VF		
DRAWN	BAG	28/OCT/10	PROTECTED GOLD MIRROR		
APPROVAL	WD	08/NOV/12	MATERIAL		REV
COPYRIGHT © 2010 BY THORLABS			N-BK7		С
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS			ITEM # CM127-050-M01	APPROX WE	іGHT kg