




NOTES:

1. SUBSTRATE:
FUSED SILICA
2. SURFACE S2 TO BE PARALLEL TO SURFACE S1 TO WITHIN <5 ARCSEC
3. COATING (APPLY ACROSS COATING APERTURE):
S1 & S2: NIR II (750-1550nm)
R(ABS) ≤1.5% @ 750 - 800nm
R(ABS) ≤1.0% @ 800 - 1550nm
R(AVG) ≤0.7% @ 750 - 1550nm
4. WAVELENGTH RANGE: 750 - 1550nm



**FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING**

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS ARE FOR REFERENCE ONLY

	S1	S2	 Edmund Optics®					
SHAPE	PLANO	PLANO						
SURFACE QUALITY	20-10	20-10	ALL DIMS IN	mm	DWG NO	11902		
TRANSMITTED WAVEFRONT (P-V)	0.10 WAVE	0.10 WAVE					SHEET	1 OF 1
CLEAR APERTURE	$\phi 20.00$	$\phi 20.00$					DWG NO	
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED						