





## NOTES/SPECIFICATIONS:

- 1. CLEAR APERTURE:  $> \emptyset$  11.43mm
- 2. SURFACE QUALITY: 40-20 SCRATCH-DIG
- 3. TRANSMITTED WAVEFRONT ERROR: <λ/4 AT 633nm
- 4. PARALLELISM: <3 arcmin
- 5. FILTER COATING (\$1):

REFLECTION BAND (R): >99% AVERAGE Rs AND Rp 1250-1400nm
TRANSMISSION BAND (T): >93% AVERAGE Ts, >95% AVERAGE Tp 1000-1175nm
45° AOI

6. AR COATING (S2)

R: <2% ABSOLUTE 1000-1175nm 45° AOI

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THOR LABS.		
	NAME	DATE	Ø 12.7mm SHORTPASS		
DRAWN	MG	03/APR/17	DICHROIC MIRROR 1200nm		n
APPROVAL	BW	09/MAY/17	UV FUSED SILICA		REV
COPYRIGHT © 2017 BY THORLABS			UV FUSED SILICA		Α
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS			DMSP1200T	APPROX WE	IGHT