



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 587.6nm
2. FOCAL LENGTH: $f=50.0\text{mm} \pm 1\%$
3. BACK FOCAL LENGTH (REF): $bf=48.2\text{mm}$
4. CLEAR APERTURE: $> \phi 11.43\text{mm}$
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION: $\leq 3\text{arcmin}$
7. DIAMETER TOLERANCE: $+0.0/-0.1\text{mm}$
8. CENTER THICKNESS TOLERANCE: $\pm 0.1\text{mm}$
9. COATING: BBAR 245-400nm, $R_{\text{avg}} < 0.5\%$ 0° AOI ON OUTER OPTICAL SURFACE

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THORLABS www.thorlabs.com	
NAME	DATE	$\phi 12.7\text{mm } f=50.0\text{mm}$ UVFS PLANO CONVEX LENS UV COATED		
DRAWN	GG	09/SEP/10	MATERIAL	REV
APPROVAL	MG	20/MAY/15	UV-GRADE FUSED SILICA	D
COPYRIGHT © 2015 BY THORLABS			ITEM #	APPROX WEIGHT
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			LA4765-UV	0.6g