



NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTH: 587.6nm
- FOCAL LENGTH: f=99.7mm ± 1%
- 2. BACK FOCAL LENGTH(REF): bf=87.0mm
- CLEAR APERTURE: >90%
- SURFACE QUALITY: 40-20 SCRATCH-DIG 5.
- 6. CENTRATION: <3arcmin
- 7. DIAMETER TOLERANCE: +0.0/-0.1mm
- 8. THICKNESS TOLERANCE: ±0.1mm
- COATING: BBAR Rayg<0.5% FROM 650nm-1050nm, 0° AOI, ON OUTER OPTICAL SURFACES

ALL DIMENSIONS ARE IN THE FORM $\frac{[in]}{mm}$

THIS DRAWING IS FOR INFORMATION ONLY NOT INTENDED FOR MANUFACTURING

			11
	NAME	DATE	
DRAWN	WD	11/19/2009	TITL
ENG APPR.	BW	11/24/2009	
MFG APPR.	DD	12/09/2009	MA1
PROPRIETARY AND CONFIDENTIAL			MAI

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF THORLABS, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF

THORLABS, INC. IS PROHIBITED.

THORLABS INC. PO BOX 366 NEWTON NJ

LE: D=75.0 F=100.0 N-BK7 B COAT PLANO CONVEX LENS

TERIAL: SIZE REV. N-BK7 $A \mid B$ SCALE: 1:1 SHEET 1 OF 1 DWG. NO. PART NO. LA1238-B 4525-E01

3 2