



NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: >90% DIAMETER
2. SURFACE ACCURACY: $\lambda/4$ AT 632.8nm OVER CLEAR APERTURE
3. SURFACE QUALITY: 40-20 SCRATCH-DIG
4. BACK SURFACE: FINE GROUND
5. THICKNESS TOLERANCE: ± 0.2 mm
6. DIAMETER TOLERANCE: + 0.0/-0.2 mm
7. COATING: PROTECTED ALUMINUM
 R_{avg} : >90% FROM 450nm - 2 μ m
 R_{avg} : >95% FROM 2 μ m - 20 μ m
 AOI: 0° TO 45°
8. DAMAGE THRESHOLD: 0.3J/cm² 10ns PULSE, 10Hz AT 1064nm

FOR INFORMATION ONLY
 NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			 www.thorlabs.com	
	NAME	DATE		
DRAWN	BAG	27/OCT/10	MATERIAL	REV
APPROVAL	WD	08/NOV/12		N-BK7
COPYRIGHT © 2010 BY THORLABS			ITEM #	APPROX WEIGHT
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			CM254-100-G01	0.007 kg