



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 587.6nm
2. FOCAL LENGTH: $f=40.1\text{mm} \pm 1\%$
3. BACK FOCAL LENGTH(REF): $bf=35.3\text{mm}$
4. CLEAR APERTURE: >90% OF DIAMETER
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION: <3arcmin
7. DIAMETER TOLERANCE: $+0.0/-0.1\text{mm}$
8. THICKNESS TOLERANCE: $\pm 0.1\text{mm}$
9. COATING: BBAR $R_{avg} < 0.5\%$ FROM 650nm-1050nm, 0° AOI, ON OUTER OPTICAL SURFACES

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION

	NAME	DATE
DRAWN	GG	28/SEP/12
APPROVAL	DD	28/SEP/12

COPYRIGHT © 2012 BY THORLABS
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS

THORLABS
www.thorlabs.com

D=25.40 F=40.00 UV FUSED SILICA PLANO CONVEX LENS, -B COAT		REV A
MATERIAL UV FUSED SILICA		
ITEM # LA4306-B	APPROX WEIGHT 0.03 kg	