







## NOTES/SPECIFICATIONS:

- 2. 3. 4. 5.
- CLEAR APERTURE: >90% DIAMETER
  SURFACE ACCURACY: \(\lambda/4\) AT 632.8nm OVER CLEAR APERTURE
  SURFACE QUALITY: 20-10 SCRATCH-DIG
  BACK SURFACE: FINE GROUND
  THICKNESS TOLERANCE: \(\pma\).2 mm
  DIAMETER TOLERANCE: \(\pma\).0/-0.2 mm
  COATING: BROADBAND HR, DIELECTRIC
  Rs and Rp >99% OVER WAVELENGTH RANGE
  AOI: 0° TO 45°

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECT		<b>→</b>	THOR Www.thorlab		
	NAME	DATE	$\phi$ 75.0mm, f= 150.0mm BROADBAN		AND
DRAWN	MG	15/JUN/11	MIRROR 1280-1600nm		
APPROVAL	PM	13/JUL/11	MATERIAL		REV
COPYRIGHT © 2010 BY THORLABS			N-BK7		Α
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF FRRORS			ITEM # C.M750-150-F04	APPROX WE	EIGHT