



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 588nm
2. FOCAL LENGTH:  $f=500.0\text{mm} \pm 1\%$
3. BACK FOCAL LENGTH (REF):  $bf=499.2\text{mm}$
4. CLEAR APERTURE:  $> \varnothing 22.86\text{mm}$
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION:  $\leq 3\text{arcmin}$
7. DIAMETER TOLERANCE:  $+0.00/-0.10\text{mm}$
8. THICKNESS TOLERANCE:  $\pm 0.1\text{mm}$
9. COATING: BBAR 245-400nm,  $R_{\text{avg}} < 0.5\%$   $0^\circ$  AOI ON OUTER OPTICAL SURFACES

FOR INFORMATION ONLY  
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			<b>THORLABS</b> <a href="http://www.thorlabs.com">www.thorlabs.com</a> $\varnothing 25.4\text{mm}$ $f=500.0\text{mm}$ UVFS BI-CONVEX LENS UV COATED	
NAME	DATE			
DRAWN	UW	29/MAY/15	MATERIAL UV GRADE FUSED SILICA	
APPROVAL	MI	29/MAY/15		
COPYRIGHT © 2015 BY THORLABS			ITEM #	APPROX WEIGHT
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			LB4453-UV	2.5kg