



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 587.6nm
2. FOCAL LENGTH: $f=100.3\text{mm} \pm 1\%$
3. BACK FOCAL LENGTH(REF): $bf=97.7\text{mm}$
4. CLEAR APERTURE: $>90\%$
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION: $<3\text{arcmin}$
7. DIAMETER TOLERANCE: $+0.0/-0.1\text{mm}$
8. THICKNESS TOLERANCE: $\pm 0.1\text{mm}$
9. COATING: VAR R $<0.25\%$ PER SURFACE FOR 532nm & 1064nm

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION

	NAME	DATE
DRAWN	GG	01/OCT/12
APPROVAL	DD	01/OCT/12

COPYRIGHT © 2012 BY THORLABS
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS

THORLABS
www.thorlabs.com

D=25.4 F=100 UV FUSED SILICA
PLANO CONVEX LENS, -YAG COAT
MATERIAL UV FUSED SILICA REV A

ITEM # LA4380-YAG APPROX WEIGHT 0.03 kg