



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 587.6nm
2. FOCAL LENGTH: $f=4.0\text{mm} \pm 1\%$
3. BACK FOCAL LENGTH (REF): $bf=3.31\text{mm}$
4. CLEAR APERTURE: $>1.8\text{mm}$
5. SURFACE QUALITY: 60-40 SCRATCH-DIG
6. CENTRATION: ≤ 5 arcmin
7. DIAMETER TOLERANCE: $+0.00/-0.02\text{mm}$
8. THICKNESS TOLERANCE: $\pm 0.03\text{mm}$
9. COATING: BBAR $R_{\text{avg}} < 0.5\%$ FROM 350-700nm, AOI: 0°

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			 www.thorlabs.com	
NAME	DATE			
DRAWN	YB	24/JAN/19	$\varnothing 2\text{mm } f=4\text{mm}$ UV FUSED SILICA PLANO CONVEX LENS, -A COAT	
APPROVAL	NE	24/JAN/19	MATERIAL	REV
COPYRIGHT © 2019 BY THORLABS <small>VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS</small>			UV FUSED SILICA	A
			ITEM #	APPROX WEIGHT
			LA4024-A	0.006 g