



NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: >90% DIAMETER
2. SURFACE ACCURACY: $\lambda/4$ AT 632.8nm OVER CLEAR APERTURE
3. SURFACE QUALITY: 40-20 SCRATCH-DIG
4. BACK SURFACE: FINE GROUND
5. THICKNESS TOLERANCE: ± 0.2 mm
6. DIAMETER TOLERANCE: + 0.0/-0.2 mm
7. COATING: PROTECTED GOLD
Ravg: >96% FROM 800nm - 20 μ m
AOI: 0° TO 45°
8. DAMAGE THRESHOLD: 2J/cm² 10ns PULSE, 10Hz AT 1064nm

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			 www.thorlabs.com	
NAME	DATE			
DRAWN	BAG	28/OCT/10	$\varnothing 75.0$ mm, f= 150.0mm CONCAVE PROTECTED GOLD MIRROR	
APPROVAL	WD	08/NOV/12		
COPYRIGHT © 2010 BY THORLABS			MATERIAL	REV
			N-BK7	C
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			ITEM #	APPROX WEIGHT
			CM750-150-M01	0.19 kg