





NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTH: 587.6nm
 FOCAL LENGTH: f=75.3mm ± 1%
 BACK FOCAL LENGTH(REF): bf=72.2mm
 CLEAR APERTURE: >90% OF DIAMETER
 SURFACE QUALITY: 40-20 SCRATCH-DIG

- CENTRATION: <3 arcmin
 DIAMETER TOLERANCE: +0.0/-0.1 mm
 THICKNESS TOLERANCE: ±0.1 mm
 COATING: BBAR Rayg<0.5% FROM 650nm-1050nm,
 0° AOI, ON OUTER OPTICAL SURFACES 6. 7. 8. 9.

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

	DRAWING PROJECTION			THORLABS.com		
		NAME	DATE	D=25.40 F=75.00 UV FUSED SILICA PLANO CONVEX LENS, -B COAT		ICA
	DRAWN	GG	28/SEP/12			ΑT
	APPROVAL	DD	28/SEP/12	MATERIAL	C A	REV
	COPYRIGHT © 2012 BY THORLABS			UV FUSED SILICA		Α
	VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS			LA4725-B	0.03 k	ight (g