





NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTH: 587.6nm
 FOCAL LENGTH: f=35.1mm ± 1%
 BACK FOCAL LENGTH(REF): bf=29.5mm
 CLEAR APERTURE: >90% OF DIAMETER
 SURFACE QUALITY: 40-20 SCRATCH-DIG

- CENTRATION: <3 arcmin
 DIAMETER TOLERANCE: +0.0/-0.1 mm
 THICKNESS TOLERANCE: ±0.1 mm
 COATING: BBAR Ravg<0.5% FROM 350nm-700nm,
 0° AOI, ON OUTER OPTICAL SURFACES

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

	DRAWING PROJECTION			THORLASS www.thorlabs.com			
		NAME	DATE	D=25.40 F=35.00 UV			
	DRAWN	GG	28/SEP/12	PLANO CONVEX LE	NS, -A CC	ΑT	
	APPROVAL	DD	28/SEP/12	UV FUSED SILICA		REV ∆	
	COPYRIGHT © 2012 BY THORLABS				_	/ \	
	VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS			LA4052-A	0.03 k	(g	