

NOTES:



1. SUBSTRATE:
N-BK7
2. CENTERING TOLERANCE (AT 587.6nm):
BEAM DEVIATION: ≤ 2 ARCMIN
3. COATING (APPLY ACROSS CLEAR APERTURE):
NIR
S1, S2, S3, & S4: R(AVG) $< 0.5\%$ @ 720 - 1080nm
S5: MULTILAYER DIELECTRIC TO ACHIEVE:
TRANSMISSION $> 27\% \pm 5\%$
POLARIZATION $< 6\%$

FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING

4. FINE GROUND SURFACE

5. ELEMENTS TO BE CEMENTED WITH NORLAND OPTICAL ADHESIVE NOA 61

6. MARK IDENTIFIES BEAMSPLITTED COATED RIGHT ANGLE PRISM



SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS ARE FOR REFERENCE ONLY

	S1	S2
SHAPE	PLANO	PLANO
SURFACE ACCURACY	$\lambda/8$	$\lambda/8$
SURFACE QUALITY	40-20	40-20
CLEAR APERTURE	$> 90\%$	$> 90\%$



ALL DIMS IN

mm

EO® Edmund Optics®

TITLE

20mm NIR, 70R/30T, Non-Polarizing Cube
Beamsplitter

DWG NO

13439

SHEET
1 OF 1