


PC4QM




Description

The PC4QM co-fired stack consists of a series of stacked piezoelectric ceramic layers separated by electrodes that extend across the full surface of layer. The entire stack is sintered as a single unit. This construction provides a free stroke displacement significantly larger than discrete piezo stacks, which are constructed of piezo chips epoxied together. As the electrodes span the entire surface of the piezoelectric layers, the entire surface is active and responds to the driving voltage.

The PC4QM offers a maximum displacement of $9.1 \mu\text{m} \pm 15\%$. A green wire is soldered to the electrode that should receive positive bias; the other electrode should be grounded.


Specifications

PC4QM ^a	
Drive Voltage Range	0 to 150 V
Displacement (Free Stroke) at 150 V ^b	$9.1 \mu\text{m} \pm 15\%$
Hysteresis	$\leq 15\%$ (See Graph on Next Page)
Load for Maximum Displacement ^c	400 N (90 lbs)
Recommended Preload	<400 N (90 lbs)
Blocking Force at 150V	1000 N (220 lbs)
Resonant Frequency	$115 \text{ kHz} \pm 10\%$ (No Load)
Impedance at Resonant Frequency	300 m Ω
Anti-Resonant Frequency	170 kHz
Dissipation Factor ^d	<2.0%
Capacitance ^d	$650 \text{ nF} \pm 15\%$
Operating Temperature	-25 to 110 °C
Curie Temperature	230 °C
Dimensions	Width 1: 6.5 mm + 0/-0.5 mm Width 2: 6.5 mm + 0/-0.5 mm Length: 10.0 mm $\pm 5 \mu\text{m}$



- All specifications are quoted at 25 °C, unless otherwise stated.
- The “free stroke” displacement corresponds to no load.
- The displacement may vary slightly for different loads, and the maximum displacement occurs when the load for maximum displacement is used.
- Specified at 1 kHz, 1 V_{RMS}.



Drawing



June 24, 2020

CTN012214-S01, Rev C

Typical Performance Plots



The temperature increase of the stack was measured after applying a sine-wave driving voltage, with maximum and peak-to-peak amplitudes of 150 V, at the specified frequency for 10 minutes.

Operation

Electrical Considerations

- The electrode attached to the green wire should be connected to positive (+) drive voltage, and the opposite electrode attached to the white wire should be grounded. The maximum drive voltage is 150 V. Exceeding 150 V will decrease the device's lifespan and may cause mechanical failure. Reverse biasing the device may cause mechanical failure.
- After driving, the piezo is fully charged. Directly connecting the green and white wires has the risk of electricity discharging, spark, and even failure. We recommend using a resistor (>1 kΩ) between the green and white wires to release the charge.

Attaching Devices to the Piezo

- Any epoxy which cures at a temperature lower than 80 °C is safe to use. We recommend Thorlabs Item #s 353NDPK or TS10. Loctite Hysol 9340 is also usable.
- Loads should only be attached to the uncoated faces since the polymer-coated faces do not translate. Attaching a load to the coated faces may lead to mechanical failure.

Storage Instructions

- Do not store the device at temperatures above 110 °C.
- Do not store the device in humid environments. The relative humidity (RH) should be less than 40%.
- Do not immerse the device in organic solvents.
- Do not use the device around combustible gases or liquids.