



NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: >90% DIAMETER
2. SURFACE ACCURACY:  $\lambda/4$  AT 632.8nm OVER CLEAR APERTURE
3. SURFACE QUALITY: 40-20 SCRATCH-DIG
4. BACK SURFACE: FINE GROUND
5. THICKNESS TOLERANCE:  $\pm 0.2$  mm
6. DIAMETER TOLERANCE: + 0.0/-0.2 mm
7. COATING: PROTECTED SILVER  
 $R_{\text{avg}}$ : >97.5% FROM 450nm - 2 $\mu\text{m}$   
 $R_{\text{avg}}$ : >96% FROM 2 $\mu\text{m}$  - 20 $\mu\text{m}$   
 AOI: 0° TO 45°
8. DAMAGE THRESHOLD: 3J/cm<sup>2</sup> 10ns PULSE, 10Hz AT 1064nm

FOR INFORMATION ONLY  
 NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			 www.thorlabs.com	
NAME	DATE			
DRAWN	BAG	28/OCT/10	$\phi 25.4\text{mm}$ , f= 25.0mm CONCAVE PROTECTED SILVER MIRROR	
APPROVAL	WD	08/NOV/12	MATERIAL	REV
COPYRIGHT © 2010 BY THORLABS			N-BK7	C
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			ITEM #	APPROX WEIGHT
			CM254-025-P01	0.007 kg