





NOTES/SPECIFICATIONS:

CLEAR APERTURE: > \$\psi 22.86mm\$
SURFACE QUALITY: 40-20 SCRATCH-DIG
TRANSMITTED WAVEFRONT ERROR: <\lambda/4 AT 633nm
PARALLELISM: <3 arcmin
FILTER COATING (S1):
REFLECTION BAND (R): >95% AVERAGE, >90% ABSOUTE 505-800nm
TRANSMISSION BAND (T): >90% AVERAGE, >85% ABSOLUTE 380-475nm
45° AOI
AR COATING (S2):
R: <2% ABSOLUTE 380-475nm 45° AOI

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

				,		
	DRAWING PROJECTION			THOR LABS		
		NAME	DATE	Ø 25.4mm SHORTPASS		
	DRAWN	MG	18/MAY/16	DICHROIC MIRROR 490nm		1
	APPROVAL	DD	08/JUNE/16	MATERIAL	\sim \wedge	REV
	COPYRIGHT © 2016 BY THORLABS			UV FUSED SILICA		Α
	VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF FRRORS			ITEM # DMSP490	APPROX WE	IGHT
				2.7.131 170	9	