



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 587.6nm
2. FOCAL LENGTH: $f=125.0\text{mm} \pm 1\%$
3. BACK FOCAL LENGTH (REF): $bf=122.7\text{mm}$
4. CLEAR APERTURE: $> \varnothing 22.86\text{mm}$
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION: $\leq 3\text{arcmin}$
7. DIAMETER TOLERANCE: $+0.0/-0.1\text{mm}$
8. CENTER THICKNESS TOLERANCE: $\pm 0.1\text{mm}$
9. COATING: BBAR 245-400nm, $R_{\text{avg}} < 0.5\% \ 0^\circ \ \text{AOI}$
ON OUTER OPTICAL SURFACE

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			 www.thorlabs.com	
NAME	DATE	$\varnothing 25.4\text{mm} \ f=125.0\text{mm}$ UVFS PLANO CONVEX LENS, UV COATED		
DRAWN	GG	09/SEP/10	MATERIAL	
APPROVAL	MG	20/MAY/15	UV GRADE FUSED SILICA	REV D
COPYRIGHT © 2015 BY THORLABS VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			ITEM #	APPROX WEIGHT
			LA4236-UV	3.2g