



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 587.6nm
2. FOCAL LENGTH: $f=29.9\text{mm}$
3. BACK FOCAL LENGTH(REF): $bf=27.8\text{mm}$
4. CLEAR APERTURE: >90% OF DIAMETER
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION: <3arcmin
7. DIAMETER TOLERANCE: +0.0/-0.1mm
8. THICKNESS TOLERANCE: $\pm 0.1\text{mm}$
9. COATING: BBAR $R_{\text{avg}} < 0.5\%$ FROM 1050-1700nm, AOI: 0° , ON OUTER OPTICAL SURFACES

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

| | | | | |
|---|------|-----------|--|---------------|
| DRAWING PROJECTION | | | THORLABS www.thorlabs.com $\varnothing=12.7\text{mm}$ $f=30\text{mm}$ N-BK7 PLANO CONVEX LENS, -C COAT | |
| NAME | DATE | | | |
| DRAWN | MG | 22/AUG/13 | MATERIAL N-BK7 | |
| APPROVAL | DD | 03/OCT/13 | | |
| COPYRIGHT © 2013 BY THORLABS | | | ITEM # | APPROX WEIGHT |
| VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS | | | LA1289-C | 3g |