



SECTION A-A
SCALE 2:1

NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: $> \varnothing 22.86\text{mm}$
2. SURFACE IRREGULARITY (S1): $\leq \lambda/4$ AT 633nm OVER CLEAR APERTURE
3. BACK SURFACE (S2): UNIFORM FINE GRIND #12-#20 GRIT
4. SURFACE QUALITY(S1): 20-10 SCRATCH-DIG
5. THICKNESS TOLERANCE: $\pm 0.1\text{ mm}$
6. DIAMETER TOLERANCE: $+0.0/-0.2\text{ mm}$
7. DESIGN WAVELENGTH RANGE: 750-1100nm
8. COATING(S1): BROADBAND HR, DIELECTRIC
 R_s and $R_p > 99\%$ AVERAGE OVER WAVELENGTH RANGE
 AOI: 0° TO 45°

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			 www.thorlabs.com $\varnothing 25.4\text{mm}$, $f=750\text{mm}$ BROADBAND MIRROR 750-1100nm	
NAME	DATE			
DRAWN	YB	16/APR/18	MATERIAL N-BK7	
APPROVAL	DD	16/APR/18		
COPYRIGHT © 2018 BY THORLABS			ITEM #	APPROX WEIGHT
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			CM254-750-E03	7.67 g
			REV	A