NOTES:

1. SUBSTRATE: Fused Silica (Corning 7980)

2. ROHS: COMPLIANT


3. SURFACE S2 TO BE PARALLEL TO SURFACE S1 WITHIN <5 ARCMIN


4. COATING (APPLY ACROSS CLEAR APERTURE)


\$1 & \$2: NONE

5. TRANSMITTED WAVEFRONT DISTORTION: ≤ 1λ









## DO NOT MANUFACTURE PARTS TO THIS DRAWING

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE DIMENSIONS ARE FOR REFERENCE ONLY

	\$1	\$2		
SHAPE	PLANO	PLANO		
SURFACE QUALITY	60-40	60-40		
CLEAR APERTURE	Ø 22.50	Ø 22.50		
BEVEL	PROTECTED AS NEEDED	PROTECTED AS NEEDED		

THIRD ANGLE PROJECTION	$\phi \Leftrightarrow$	TI
ALL DIMS IN	mm	D'

	Edmund Optics®
TITLE	25mm Dia. 5mm Thick Uncoated, 1λ Fused

1 OF 1

<del>\</del>	TITLE	25mm Dia. 5mm Thick Uncoated, 1λ F Silica Window	used
mm	DWG NO	19840	SHEET 1 OF 1