



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 4 μ m
2. FOCAL LENGTH: $f = -50.0\text{mm} \pm 2\%$
3. BACK FOCAL LENGTH(REF): $bf = -49.2\text{mm}$
4. CLEAR APERTURE: $> \varnothing 22.86\text{mm}$
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION: $< 3\text{arcmin}$
7. DIAMETER TOLERANCE: $\pm 0.0/-0.1\text{mm}$
8. THICKNESS TOLERANCE: $\pm 0.1\text{mm}$

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

| | | | | |
|---|------|--|-------------------------------------|-------------------------------------|
| DRAWING PROJECTION | | | THORLABS www.thorlabs.com | |
| NAME | DATE | CaF ₂ - MENISCUS LENS, $\varnothing 25.4\text{mm}$, $f = -50\text{mm}$, UNCOATED | | |
| DRAWN | KMR | 21/MAY/18 | MATERIAL | VACUUM UV GRADE CALCIUM FLUORIDE |
| APPROVAL | BW | 21/MAY/18 | ITEM # | LF5414 |
| COPYRIGHT © 2018 BY THORLABS | | | APPROX WEIGHT | 10.3g |
| VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS | | | REV | B |