



NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: $> \varnothing 45.72\text{mm}$
2. SURFACE IRREGULARITY (S1): $\leq \lambda/4$ AT 633nm OVER CLEAR APERTURE
3. BACK SURFACE (S2): UNIFORM FINE GRIND #12-#20 GRIT
4. SURFACE QUALITY(S1): 40-20 SCRATCH-DIG
5. THICKNESS TOLERANCE: $\pm 0.1\text{ mm}$
6. DIAMETER TOLERANCE: $+0.0/-0.2\text{ mm}$
7. COATING(S1): PROTECTED SILVER
 $R_{\text{avg}}: >97.5\%$ FROM 450nm-2 μm
 $R_{\text{avg}}: >96\%$ FROM 2 μm -20 μm
 AOI: 0° TO 45°

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			 www.thorlabs.com $\varnothing 50.8\text{mm}$, f=500mm CONCAVE PROTECTED SILVER MIRROR	
NAME	DATE			
DRAWN	YB	16/APR/18	MATERIAL	
APPROVAL	DD	16/APR/18		
COPYRIGHT © 2018 BY THORLABS			N-BK7	REV A
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			ITEM #	APPROX WEIGHT
			CM508-500-P01	46.61 g