



NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: >90% DIAMETER
2. SURFACE ACCURACY: $\lambda/4$ AT 632.8nm OVER CLEAR APERTURE
3. SURFACE QUALITY: 40-20 SCRATCH-DIG
4. BACK SURFACE: FINE GROUND
5. THICKNESS TOLERANCE: $\pm 0.2\text{ mm}$
6. DIAMETER TOLERANCE: $+ 0.0/-0.2\text{ mm}$
7. COATING: PROTECTED SILVER
Ravg: >97.5% FROM 450nm - 2 μm
Ravg: >96% FROM 2 μm - 20 μm
AOI: 0° TO 45°
8. DAMAGE THRESHOLD: 3J/cm² 10ns PULSE, 10Hz AT 1064nm

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THORLABS www.thorlabs.com	
NAME	DATE			
DRAWN	BAG	28/OCT/10	$\phi 12.7\text{mm}$, f= 25.0mm CONCAVE PROTECTED SILVER MIRROR	
APPROVAL	WD	08/NOV/12		
COPYRIGHT © 2010 BY THORLABS			MATERIAL	REV
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			N-BK7	C
ITEM #		APPROX WEIGHT		
CM127-025-P01		0.002 kg		