



NOTES/SPECIFICATIONS:

1. DESIGN WAVELENGTH: 587.6nm
2. FOCAL LENGTH: $f=30.0\text{mm} \pm 1\%$
3. BACK FOCAL LENGTH (REF): $bf=27.7\text{mm}$
4. CLEAR APERTURE: $> \varnothing 11.43\text{mm}$
5. SURFACE QUALITY: 40-20 SCRATCH-DIG
6. CENTRATION: $\leq 3\text{arcmin}$
7. DIAMETER TOLERANCE: $+0.0/-0.1\text{mm}$
8. CENTER THICKNESS TOLERANCE: $\pm 0.1\text{mm}$
9. COATING: BBAR 245-400nm, $R_{\text{avg}} < 0.5\% \text{ } 0^\circ \text{ AOI}$
ON OUTER OPTICAL SURFACE

FOR INFORMATION ONLY
NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THORLABS www.thorlabs.com $\varnothing 12.7\text{mm } f=30.0\text{mm}$ UVFS PLANO CONVEX LENS UV COATED	
DRAWN	GG	DATE		
APPROVAL	MI	DATE	20/MAY/15	MATERIAL
COPYRIGHT © 2015 BY THORLABS VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS				UV GRADE FUSED SILICA ITEM # LA4936-UV
				APPROX WEIGHT 0.7g
				REV D