




NOTES:

1. SUBSTRATE: UV GRADE FUSED SILICA
2. COATING (APPLY ACROSS CLEAR APERTURE)
 S1 & S2: RABS $\leq 1.0\%$ @ 350 - 450nm
 RAVG $\leq 1.5\%$ @ 250 - 700nm
3. SURFACE S2 TO BE PARALLEL WITH S1 TO WITHIN < 5 ARCSEC

 FINE GRIND SURFACE

5. RoHS COMPLIANT



**FOR INFORMATION ONLY:
DO NOT MANUFACTURE
PARTS TO THIS DRAWING**

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS ARE FOR REFERENCE ONLY

	S1	S2
SHAPE	PLANO	PLANO
SURFACE QUALITY	20-10	20-10
CLEAR APERTURE	Ø4.00	Ø4.00
BEVEL	PROTECTIVE AS NEEDED	PROTECTIVE AS NEEDED



ALL DIMS IN mm

 **Edmund Optics®**

TITLE 5mm DIA., 1mm THICK, UV-VIS COATED $\lambda/10$ FUSED SILICA WINDOW

DWG NO 48062

SHEET 1 OF 1