



## NOTES/SPECIFICATIONS:

- CLEAR APERTURE: >90% DIAMETER

- 2. 3. 4. 5.

- CLEAR APERTURE: >90% DIAMETER
  SURFACE ACCURACY: \(\)/4 AT 632.8nm OVER CLEAR APERTURE
  SURFACE QUALITY: 20-10 SCRATCH-DIG
  BACK SURFACE: FINE GROUND
  THICKNESS TOLERANCE: \(\)±0.2 mm
  DIAMETER TOLERANCE: \(\)±0.0/-0.2 mm
  COATING: BROADBAND HR, DIELECTRIC
  Rs and Rp >99% OVER WAVELENGTH RANGE
  AOI: 0° TO 45°

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THOR LABS		
	NAME	DATE	$\emptyset$ 25.4mm, f= 25.0mm BROADB.		ΑΝΓ
DRAWN	MG	15/JUN/11	MIRROR 400-750nm		
APPROVAL	PM	13/JUL/11	MATERIAL		REV
COPYRIGHT © 2010 BY THORLABS			N-BK7		Α
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS			ITEM # CM254-025-E02	APPROX WE 0.007	ıgнт kg