



NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: $> \varnothing 22.86\text{mm}$
2. SURFACE IRREGULARITY (S1): $\leq \lambda/4$ AT 633nm OVER CLEAR APERTURE
3. BACK SURFACE (S2): UNIFORM FINE GRIND #12-#20 GRIT
4. SURFACE QUALITY(S1): 20-10 SCRATCH-DIG
5. THICKNESS TOLERANCE: $\pm 0.1\text{ mm}$
6. DIAMETER TOLERANCE: $+0.0/-0.2\text{ mm}$
7. DESIGN WAVELENGTH RANGE: 400-750nm
8. COATING(S1): BROADBAND HR, DIELECTRIC
 R_s and $R_p > 99\%$ AVERAGE OVER WAVELENGTH RANGE
 AOI: 0° TO 45°

FOR INFORMATION ONLY
 NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			 www.thorlabs.com	
NAME	DATE			
DRAWN	YB	16/APR/18	$\varnothing 25.4\text{mm}$, $f=250\text{mm}$ BROADBAND MIRROR 400-750nm	
APPROVAL	DD	16/APR/18	MATERIAL	REV
COPYRIGHT © 2018 BY THORLABS			N-BK7	A
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			ITEM #	APPROX WEIGHT
			CM254-250-E02	7.73 g