



## NOTES/SPECIFICATIONS:

- DESIGN WAVELENGTH: 587.6nm
- FOCAL LENGTH: f=10.0mm
- BACK FOCAL LENGTH(REF): bf=8.3mm
- CLEAR APERTURE: >90% OF DIAMETER
- SURFACE QUALITY: 40-20 SCRATCH-DIG
- 6. 7. 8.
- CENTRATION: <3arcmin
  DIAMETER TOLERANCE: +0.0/-0.1mm
- THICKNESS TOLERANCE: ±0.1mm
  COATING: BBAR Ravg<0.5% FROM 1050-1700nm, AOI: 0°,
  ON OUTER OPTICAL SURFACES

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THORLABS www.thorlabs.com		
	NAME	DATE	$\phi$ =6mm f=10mm N-BK7		
DRAWN	MG	22/AUG/13			ΑT
APPROVAL	DD	03/OCT/13	MATERIAL		REV
COPYRIGHT © 2013 BY THORLABS		BY THORLABS	N-BK7		С
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS			LA1116-C	APPROX WE	IGHT