







NOTES/SPECIFICATIONS:

- CLEAR APERTURE: >90% DIAMETER
 SURFACE ACCURACY: \(\lambda/4\) AT 632.8nm OVER CLEAR APERTURE
 SURFACE QUALITY: 40-20 SCRATCH-DIG
 BACK SURFACE: FINE GROUND
 THICKNESS TOLERANCE: \(\pma\).2 mm
 DIAMETER TOLERANCE: \(\pma\).0/-0.2 mm
 COATING: PROTECTED GOLD
 Ravg: \(\pma\)96% FROM 800nm 20\(\pm\)
 AOI: 0° TO 45°
 DAMAGE THRESHOLD: 2J/cm² 10ns PULSE, 10Hz AT 1064nm
- 8.

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

| DRAWING PROJECTION | | | THORLABS.com | |
|--|------|-----------|---------------------------|------------|
| | NAME | DATE | Ø 12.7mm, f= 12.0mm CONCA | VF |
| DRAWN | BAG | 28/OCT/10 | PROTECTED GOLD MIRROR | |
| APPROVAL | WD | 08/NOV/12 | | REV |
| COPYRIGHT © 2010 BY THORLABS | | | N-BK7 | С |
| VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS | | | TIEM # APPROX WEI 0.002 k | IGHT (a |