



## NOTES/SPECIFICATIONS:

- 2. 3. 4. 5.

- 6. 7.
- 8.
- DESIGN WAVELENGTH: 587.6 nm
  FOCAL LENGTH: f=301.1 mm ± 1%
  BACK FOCAL LENGTH(REF): bf=299.3 mm
  CLEAR APERTURE: > Ø 22.86 mm
  SURFACE QUALITY: 40-20 SCRATCH-DIG
  CENTRATION: <3 arcmin
  DIAMETER TOLERANCE: +0.0/-0.1 mm
  THICKNESS TOLERANCE: ±0.1 mm
  COATING: VAR R<0.25% PER SURFACE FOR 532/1064 nm

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THORLABS.com		
	NAME	DATE	$\emptyset$ 25.4 mm, f=300 mm UV FUSED SIL		ICA
DRAWN	JAC	22/JUL/20	PLANO CÓNVEX LENS, YAG COATIN		
APPROVAL	DD	29/JUL/20	MATERIAL UV FUSED SILICA		REV
COPYRIGHT © 2020 BY THORLABS			UV TUSED SILICA		Α
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS			LA4579-YAG	APPROX WE	IGHT