



NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: $> \varnothing 22.86\text{mm}$
2. SURFACE IRREGULARITY (S1): $\leq \lambda/4$ AT 633nm OVER CLEAR APERTURE
3. BACK SURFACE (S2): UNIFORM FINE GRIND #12-#20 GRIT
4. SURFACE QUALITY(S1): 20-10 SCRATCH-DIG
5. THICKNESS TOLERANCE: $\pm 0.1\text{ mm}$
6. DIAMETER TOLERANCE: $+0.0/-0.2\text{ mm}$
7. DESIGN WAVELENGTH RANGE: 750-1100nm
8. COATING(S1): BROADBAND HR, DIELECTRIC
 R_s and $R_p > 99\%$ AVERAGE OVER WAVELENGTH RANGE
 AOI: 0° TO 45°

FOR INFORMATION ONLY
 NOT FOR MANUFACTURING PURPOSES

| | | | | |
|--|------|-----------|--|---------------|
| DRAWING PROJECTION | | | www.thorlabs.com | |
| NAME | DATE | | | |
| DRAWN | YB | 16/APR/18 | $\varnothing 25.4\text{mm}$, $f=500\text{mm}$ BROADBAND MIRROR 750-1100nm | |
| APPROVAL | DD | 16/APR/18 | MATERIAL | REV |
| COPYRIGHT © 2018 BY THORLABS <small>VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS</small> | | | N-BK7 | A |
| | | | ITEM # | APPROX WEIGHT |
| | | | CM254-500-E03 | 7.68 g |