

## NOTES/SPECIFICATIONS:

- CLEAR APERTURE: >90% DIAMETER

- 2. 3. 4. 5. 6. 7.
- CLEAR APERTURE: >90% DIAMETER
  SURFACE ACCURACY: \(\)/4 AT 632.8nm OVER CLEAR APERTURE
  SURFACE QUALITY: 20-10 SCRATCH-DIG
  BACK SURFACE: FINE GROUND
  THICKNESS TOLERANCE: \(\)±0.2 mm
  DIAMETER TOLERANCE: \(\)±0.0/-0.2 mm
  COATING: BROADBAND HR, DIELECTRIC
  Rs and Rp >99% OVER WAVELENGTH RANGE
  AOI: 0° TO 45°

FOR INFORMATION ONLY NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			THORLABS  www.thorlabs.com		
	NAME	DATE	$\phi$ 50.8mm, f= 50.0mm BROADBAN		AND
DRAWN	MG	15/JUN/11	MIRROR 750-1100nm		,_
APPROVAL	PM	13/JUL/11	MATERIAL		REV
COPYRIGHT © 2010 BY THORLABS			N-BK7		Α
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUNDOFF ERRORS			CM508-050-E03	APPROX WE 0.05 k	IGHT IG