





PIN 1	MOTOR (+)		
PIN 2	Vcc		
PIN 3	CHANNEL A		
PIN 4	CHANNEL B		
PIN 5	GROUND		
PIN 6	MOTOR (-)		
PIN 7	LIMIT GROUND		
PIN 8	FORWARD LIMIT		
PIN 9	REVERSE LIMIT		
PIN 10	NO CONNECTION		

NOTES: CABLE LENGTH 9" (228.6mm) PIN 1 DENOTED BY ARROW ON TOP SURFACE OF CONNECTOR LIMIT SWITCHES ARE DESIGNED FOR OVERDRIVE PROTECTION ONLY

			THORLA	BS II	VC. NEW	TON	00 NJ		
	NAME	DATE							
DRAWN	SS	02/23/09	TITLE:						
ENG APPR.	AC	10/14/03	VACUUM 25mm TRAVEL MOTORIZED ACTUATOR						
MFG APPR.	TC	10/14/03	MATERIAL:						
PROPRIETARY	AND CON	FIDENTIAL	N/A			SIZE	REV. B		
THE INFORMAT	ION CON	TAINED IN THIS							
DRAWING IS TH			SCALE: 1:1		SHEET 1 OF 1				
THORLABS, INC IN PART OR AS THE WRITTEN PI THORLABS, INC	A WHOLE	WITHOUT I OF	DWG. NO. 8631-E01	PART N	70. Z625BV				

PO BOY 344

4 3 2