



NOTES/SPECIFICATIONS:

1. CLEAR APERTURE: >90% DIAMETER
2. SURFACE ACCURACY: $\lambda/4$ AT 632.8nm OVER CLEAR APERTURE
3. SURFACE QUALITY: 40-20 SCRATCH-DIG
4. BACK SURFACE: FINE GROUND
5. THICKNESS TOLERANCE: ± 0.2 mm
6. DIAMETER TOLERANCE: + 0.0/-0.2 mm
7. COATING: UV ENHANCED ALUMINUM
 R_{avg} : >90% FROM 250nm - 450nm
 AOI: 0° TO 45°

FOR INFORMATION ONLY
 NOT FOR MANUFACTURING PURPOSES

DRAWING PROJECTION			 www.thorlabs.com	
NAME	DATE			
DRAWN	MG	07/APR/11	$\text{Ø} 50.8\text{mm}$, $f = 50.0\text{mm}$ CONCAVE UV ENHANCED ALUMINUM MIRROR	
APPROVAL	DD	12/APR/11	MATERIAL	REV
COPYRIGHT © 2010 BY THORLABS			N-BK7	A
VALUES IN PARENTHESIS ARE CALCULATED AND MAY CONTAIN ROUND OFF ERRORS			ITEM #	APPROX WEIGHT
			CM508-050-F01	0.05 kg